ISPRO

CATALOG

Industrial Products & Components







FASTENERS

PUSH-IN FITTINGS

HOSE PRODUCTS

HYDRAULIC FITTINGS

sean@is-pro.com

(541) 824-0900

4810 Table Rock Rd Ste 102 • Central Point, OR 97502

www.is-pro.com

ISPRO
INDUSTRIAL SUPPLIES
HARDWARE • FASTENERS • HOSES • CONNECTORS

sean@is-pro.com • (541) 824-0900
4810 Table Rock Rd Ste 102 • Central Point, OR 97502



Hex Bolt Grade 5



Hex Bolt Grade 8



Metric Bolt Grade 8.8



Socket Head Cap Screw



Button Head Screw



Set Screws



Carriage Bolt



Flange Bolt / Frame Bolt



Step Bolt



Washer



Lock Washer



Hex Nut



Nylon Locknut



Flange Nut



Square Nut



K Nut



Floorboard Thread Cutting Screw



Self Drilling/ Tapping Screw



Thread Cutting Screw



Rivets

ISPRO
INDUSTRIAL SUPPLIES
HARDWARE • FASTENERS • HOSES • CONNECTORS

sean@is-pro.com • (541) 824-0900
4810 Table Rock Rd Ste 102 • Central Point, OR 97502



Push in Male



Push in Elbow



Push In Female



Push in Union



Push in Bulkhead



Push in Union



Push in Tee



Push in Plug



DOT Male



DOT Elbow



DOT Union Elbow



DOT Union



DOT Tee



DOT Male



DOT Elbow



DOT Union









ISPRO
INDUSTRIAL SUPPLIES
HARDWARE • FASTENERS • HOSES • CONNECTORS

sean@is-pro.com • (541) 824-0900
4810 Table Rock Rd Ste 102 • Central Point, OR 97502


1404


1405


1501


1503


5404


5405


5406


5406-C


5406-P


5500


5501


5502


5504


5505


5601


5602


5603


5604


5605


5652


6401


6403


6405


6408


6410

ISPRO
INDUSTRIAL SUPPLIES
HARDWARE • FASTENERS • HOSES • CONNECTORS

sean@is-pro.com • (541) 824-0900
4810 Table Rock Rd Ste 102 • Central Point, OR 97502


2403


2404


2405


2406


2408


2500


2501


2502


2503


2601


2603


2605


2650


2700


2702


2705


2706


6500


6505


6400


6801


6802


6506


6602

ISPRO
INDUSTRIAL SUPPLIES
HARDWARE • FASTENERS • HOSES • CONNECTORS

sean@is-pro.com • (541) 824-0900
4810 Table Rock Rd Ste 102 • Central Point, OR 97502

SERIES 4210

TYPE 2SN-K
ONE MILLION IMPULSE CYCLE



TUBE: Type A maximum oil resistant synthetic rubber

REINFORCEMENT: Two braids of high tensile steel wire

COVER: Super abrasion resistant, **Tuff-Flex** cover
MSHA approved

TEMPERATURE: -40°F. to +212°F (-40°C to +100°C)

BRANDING: Clear Mylar / White letters with purple box

APPLICATION: Designed for high impulse, high pressure where a more abrasion resistant hose is needed. **Tuff-Flex** high abrasion resistant proprietary compound cover.

SERIES 3500

PRESSURE FLEX
SAE 100R5 TEXTILE COVER



TUBE: Type A maximum oil resistant synthetic rubber

REINFORCEMENT: One textile braid with one braid of high tensile steel wire

COVER: Extreme abrasion, oil, and weather resistant textile cover. Exceeds SAE J517 for ozone and external weathering effects

TEMPERATURE: -40°F to +212°F (-40°C to +100°C)

BRANDING: Black Mylar / white letters

APPLICATION: Medium pressure hydraulic hose suitable for petroleum based hydraulic fluids, water, oils, and pneumatic systems (textile cover).

SERIES 2112

QUICK LOCK
RUBBER PUSH-ON HOSE



TUBE: Black Nitrile

REINFORCEMENT: Braided, high tensile textile

COVER: Black Nitrile/PVC

TEMPERATURE: -40°F to +212°F (-40°C to +100°C)

BRANDING: Ink brand – white or black letters

APPLICATION: This oil resistant hose is excellent for use with air tools, to convey water, mild chemicals, and various petroleum products. No clamps or special tools needed. Special braid angle for quick and secure push-on coupling retention. Not recommended for gasoline or diesel fuels. Available in various colors for color-coding. Black cover meets MSHA 30 CFR 18.65 (Flame Resistant).

SERIES 4704NC

NON-CONDUCTIVE
SAE 100R7 (SAE J517 ANSI A92.2 COMPLIANT)



TUBE: Nylon

REINFORCEMENT: Polyester braid

COVER: Proprietary polyurethane (**"Tuff-Skin"**)
orange, non-perforated

TEMPERATURE: -40°F to +212°F (-40°C to +100°C)
Limited to +135°F (+57°C) for water-based or fire resistant fluids)
(Delta) Working length @ rated WPSI: ±2% max.

BRANDING: Ink jet

APPLICATION: Medium pressure hydraulic hose where electrical non-conductivity is required. Ideal for use on electrical utility truck hydraulic systems, aerial equipment (pickers), and rescue apparatus and tools. Bonded construction for kink resistance. Excellent abrasion and UV resistant cover **Tuff-Skin**. Meets J517 that requires less than 50 micro-amperes leakage when subjected to 75,000 volts/ft for five minutes. Complies with ANSI 92.2 for vehicle mounted aerial devices.

ISPRO
INDUSTRIAL SUPPLIES
HARDWARE • FASTENERS • HOSES • CONNECTORS

sean@is-pro.com • (541) 824-0900
4810 Table Rock Rd Ste 102 • Central Point, OR 97502


Male Pipe


Male Swivel


Female Pipe


Male Oring


Male JIC


Female JIC


Female 45


Female 90


Female L 90


Tube Repair


C61 Flange


C61 45


C61 90


Female ORFS


ORFS 45


ORFS 90


BSPP Female


BSPP Male


Metric Female


Metric Male


C62 Flange


C62 45


C62 90


Crimp Shell

ISPRO

www.is-pro.com

sean@is-pro.com

(541) 824-0900

4810 Table Rock Rd Ste 102
Central Point, OR 97502